MICROMOTORS | SLOTLESS BLDC MOTOR | SVTN A 02-1636-30-S-O



Slotless BLDC motor

High Speed - Long Lifespan - Cost Effective Low Inertia - High Efficiency - Low Noise - High Reliability



	SVTN A 02-1636-30-S-O
Nominal voltage	30 V
No load speed	40225 rpm
No load current	77 mA
Nominal speed	36958 rpm
Nominal torque	5.000 mNm
Nominal current	0.790 A
Stall torque	61.600 mNm
Stall current	8.800 A
Max. efficiency	82.200 %
Terminal resistance*	3.410 Ω
Terminal inductance*	0.170 mH
Torque constant	7.060 mNm/A
Speed constant	1353 mNm/V

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

HIGH-SPEED BRUSHLESS DC MOTORS

	SVTN A 02-1636-30-S-O
Speed/torque gradient	653.00 rpm/mNm
Mechanical time constant	3.800 ms
Rotor inertia	0.550 gcm²

Typically employed in the medical field for surgical tools, these motors merge the SVTN A Series characteristics to an optimized project for high-speed functions. Thanks to a precise balancing of the rotor and the use of special bearings, maximum stability, and low noise are guaranteed.





Winding technology without metal bodies		
Good heat dissipation and high overload		
capacity		

Long life expectancy

Light and compact, easy integration High reliability Good return on investment



Zoning de la Rivièrette, 65 7330 Saint-Ghislain (Belgium) T : +32 (0)65 76 40 40 E : service@pes-sa.com

www.pes-sa.com