## MICROMOTORS | SLOTLESS BLDC MOTOR | SVTN A 02-1656-24-S-O



Slotless BLDC motor

High Speed - Long Lifespan - Cost Effective Low Inertia - High Efficiency - Low Noise - High Reliability



	SVTN A 02-1656-24-S-O
Nominal voltage	24 V
No load speed	41670 rpm
No load current	103 mA
Nominal speed	39232 rpm
Nominal torque	6.000 mNm
Nominal current	1.200 A
Stall torque	103.000 mNm
Stall current	18.900 A
Max. efficiency	85.800 %
Terminal resistance*	1.270 Ω
Terminal inductance*	0.090 mH
Torque constant	5.470 mNm/A
Speed constant	1746 mNm/V

**Notice :** The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

## HIGH-SPEED BRUSHLESS DC MOTORS

	SVTN A 02-1656-24-S-O
Speed/torque gradient	406.00 rpm/mNm
Mechanical time constant	2.600 ms
Rotor inertia	0.610 gcm²

Typically employed in the medical field for surgical tools, these motors merge the SVTN A Series characteristics to an optimized project for high-speed functions. Thanks to a precise balancing of the rotor and the use of special bearings, maximum stability, and low noise are guaranteed.





Winding technology without metal bodies		
Good heat dissipation and high overload		
capacity		

Long life expectancy

Light and compact, easy integration High reliability Good return on investment



Zoning de la Rivièrette, 65 7330 Saint-Ghislain (Belgium) T : +32 (0)65 76 40 40 E : service@pes-sa.com

expertise in connectivity for innovative solutions

www.pes-sa.com