

Slotless BLDC motor

High Speed - Long Lifespan - Cost Effective Low Inertia - High Efficiency - Low Noise - High Reliability

Feature

	SVTN A 02-1656-36-S-H
Nominal voltage	36 V
No load speed	41311 rpm
No load current	79 mA
Nominal speed	38898 rpm
Nominal torque	6.000 mNm
Nominal current	0.800 A
Stall torque	103.000 mNm
Stall current	12.500 A
Max. efficiency	84.700 %
Terminal resistance*	2.880 Ω
Terminal inductance*	0.200 mH
Torque constant	8.270 mNm/A
Speed constant	1155 mNm/V

Notice: The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

HIGH-SPEED BRUSHLESS DC MOTORS

	SVTN A 02-1656-36-S-H
Speed/torque gradient	402.00 rpm/mNm
Mechanical time constant	2.600 ms
Rotor inertia	0.610 gcm²

Typically employed in the medical field for surgical tools, these motors merge the SVTN A Series characteristics to an optimized project for high-speed functions. Thanks to a precise balancing of the rotor and the use of special bearings, maximum stability, and low noise are guaranteed.



Benefits

Winding technology without metal bodies

Good heat dissipation and high overload capacity

Long life expectancy

Light and compact, easy integration

High reliability

Good return on investment

