MICROMOTORS | CORELESS BLDC MOTORS | SVTN A 03-2246-24-D-0



Coreless BLDC motor

Long Lifetime - High Efficiency - Low Noise - High Reliability No Cogging - Low Inertia - Cost-effective

Feature

	SVTN A 03-2246-24-D-0
Nominal voltage	24 V
No load speed	15627 rpm
No load current	140 mA
Nominal speed	12771 rpm
Nominal torque	12.000 mNm
Nominal current	1.010 A
Stall torque	82.800 mNm
Stall current	6.300 A
Max. efficiency	71.800 %
Torque constant	13.400 mNm/A
Speed constant	712 mNm/V

Notice: The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

2 POLE BRUSHLESS DC MOTORS WITH INTEGRATED ELECTRONICS

	SVTN A 03-2246-24-D-0
Speed/torque gradient	203.00 rpm/mNm
Mechanical time constant	4.800 ms
Rotor inertia	2.300 gcm²

The benefits of this technology join the simplicity of use of a brushed DC motor with the longevity of a brushless motor, maintaining cost-effectiveness and ease of integration. The lack of cogging is typical of the coreless motors and guarantees a reduced ripple torque, a linear correlation between torque, speed, and low inertia. The miniaturization of the electronics allows maintaining the diameter of the motor unvaried with a slight increase in length.



Benefits

Winding technology without metal bodies

Good heat dissipation and high overload capacity

Long life expectancy

Light and compact, easy integration

High reliability

Good return on investment

No need for external drive



Zoning de la Rivièrette, 65 7330 Saint-Ghislain (Belgium) T:+32 (0)65 76 40 40 E:service@pes-sa.com