



The CH20 Series has a compact design with a simple movement transfer.

 Feature

CH20	
Course	20-10°
Air consumption	100 mm³
Function	Normal open
Max cycle per minute	60 cycles
Weight	0.050 kg
Type	Angular 2 jaws

 Operating conditions

Working media	Filtered air
Operating pressure	3 to 7 bar
Working temperature	5 to 60°C
Lubrication	Normally not required (but if necessary, use ISOVG32 compliant lubricant)
Repeatability*	Initial value : ± 0.1 mm, after 2 million cycles : ± 0.2 mm
Lifetime	2 million cycles (with balanced load on each finger)

## ANGULAR TYPE SMALL GRIPPER, ANGLE 20~-10°

\*The values of gripping force in the above table indicates pressure at the top edge of the fingers when gripping with pressure of 5 bar.

**Notice :** The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

This simple design enables long term use.



### Advantages

Compact-Lightweight-Fast

Silent mechanism

Quick and simple integration

Large opening angle

Position sensors



### Benefits

No maintenance

Very short cycle time

Excellent power/volume ratio

Low air consumption



**pes**

product  
engineering  
services

Zoning de la Rivière, 65  
7330 Saint-Ghislain (Belgium)

T : +32 (0)65 76 40 40  
E : service@pes-sa.com