MICROMOTORS | CORELESS BLDC MOTORS | SVTN A 03-2854-24-D-0



Coreless BLDC motor

Long Lifetime - High Efficiency - Low Noise - High Reliability No Cogging - Low Inertia - Cost-effective



	SVTN A 03-2854-24-D-0
Nominal voltage	24 V
No load speed	6700 rpm
No load current	76 mA
Nominal speed	5157 rpm
Nominal torque	18.000 mNm
Nominal current	0.620 A
Stall torque	78.100 mNm
Stall current	2.430 A
Max. efficiency	67.800 %
Torque constant	33.100 mNm/A
Speed constant	288 mNm/V

Notice: The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

2 POLE BRUSHLESS DC MOTORS WITH INTEGRATED ELECTRONICS

	SVTN A 03-2854-24-D-0
Speed/torque gradient	85.70 rpm/mNm
Mechanical time constant	4.700 ms
Rotor inertia	5.200 gcm²

The benefits of this technology join the simplicity of use of a brushed DC motor with the longevity of a brushless motor, maintaining cost-effectiveness and ease of integration. The lack of cogging is typical of the coreless motors and guarantees a reduced ripple torque, a linear correlation between torque, speed, and low inertia. The miniaturization of the electronics allows maintaining the diameter of the motor unvaried with a slight increase in length.





Zoning de la Rivièrette, 65 7330 Saint-Ghislain (Belgium) T : +32 (0)65 76 40 40 E : service@pes-sa.com

expertise in connectivity for innovative solutions

www.pes-sa.com