



Hysteresis-free performance and accuracy in arcseconds for even the most demanding applications.

System Data

GMI-ANG-096	
Type	Axial, frameless, true absolute Giant Magneto Impedance encoder GMITechnology-FLUX GmbH proprietary
Standard Resolution	23 bits
ENOB in entire mounting tolerance range	21 bits
High Accuracy	$\pm 8''$, 0.002° , $\pm 40\mu\text{rad}$
Standard Accuracy	$\pm 14''$, 0.004° , $\pm 70\mu\text{rad}$
Thickness	10.80
Hysteresis	none
Repeatability	1 resolution count
Position update rate and signal latency	Real-time
Power-up Time	max. 0.8 sec

Electrical Data

Supply voltage	OptionAV: min. 4.35Vdc. max. 36Vdc Option5V: min. 4.35Vdc. max. 6Vdc Option24V: min. 6Vdc. Max. 30Vdc
----------------	---

Reverse polarity protection	yes
Current Consumption	max. 150 mA @ 25 Vdc, max. 140 mA @ 24 Vdc

Mechanical Data

Stator Base Material	Stainless steel CTE ~ 10 ppm/°C
Stator Weight	220.00 g
Rotor Base Material	0
Rotor Weight	115.00 g
Vibration	EN 60068-2-6, 20 g, 55 .. 2000 Hz
Shock	EN 60068-2-27, 200 g, 6 ms

Mounting Tolerances

Nominal Axial (air-gap)	0.30 mm
Axial Tolerance	0.25 mm
Radial Tolerances	0.20 mm

Environmental Data

Temperature Range - Standard Operating	-20°C .. +85°C
Temperature Range - Standard Storage	-20°C .. +85°C
Temperature Range - Extended Operating	-40°C .. +105°C
Temperature Range - Extended Storage	-55°C .. +125°C
Ingress Protection	IP67
EMC Immunity	complies with EN IEC 61000-6-2
EMC Emission	complies with EN IEC 61000-6-4

Advantages

Plug-n-play

No field calibration required

Wide mounting tolerances

High accuracy

Benefits

Low installation cost

Low integration effort

Easy installation