


variables/V-color

Robot Tool Changers || Sigma 3.1



Feature

	Master Adaptor	Tool Adaptor
Reference	S3.1R-XXX	S3.1T-XXX
Payload	360 kg	

	Master Adaptor	Tool Adaptor
Moment - Mx, My	2000 Nm	
Moment - Mz	2075 Nm	
Size	60x268x321 mm	60x268x321 mm
Weight	7.340 kg	5.130 kg
Couple/uncouple port	1/4" BSPP	n/a
Repeatability - X, Y	0.020 mm	
Repeatability - Z	0.013 mm	



Operating conditions

Operating temperature	5-60°C
Operating pressure	6 bar ±1
User pneumatic pressure	6 bar ±1

Sigma the foolproof tool changer range

Heavy Payload Tool Changers are gathered within Sigma Series. They allow handling payloads from 350kg till 800kg and are particularly suited for various applications such as spot welding, material handling, machine loading/unloading, mold changing, docking systems, pallet coupling systems, pick and place operations, press transfer.

Sigma Series tool changers have a modular design allowing them to suit any kind of application. Indeed, our range of standard module coupled with our custom modules offer increase the Sigma tool changers capabilities enabling them to meet many different needs.

Sigma 3.1 tool changers have a unique six-sided design allowing to accommodate more utilities. The wide range of supported communication systems and their ability to connect directly to your robot face plate, eliminating adaptor plate make them an easy-to-integrate solution while meeting the most complex applicative needs.



Advantages

- Unique wear-compensating, fail-safe cam latching mechanism
- Emergency manual unlock feature
- Higher payload capacity – up to 360 kg
- Unique six-sided design accommodates more utilities



Benefits

- A Sigma 3.1 and Sigma 5.1 common profile provides modularity and allows for interchangeability of utility modules
- Eliminates adaptor plates for lower weights, and increased strength and efficiency
- Low profile reduces inertial forces
- Supports wide variety of servo tools and bus communications



p e s

product
engineering
services

expertise in connectivity