variables/V-color

Slip Ring | 42 circuits | SVTS C 10-U-A-06/36



Slip ring for transmission of electrical power and/or electrical signals with through hole for shaft or rotary union.



SVTS C 10-U-A-06/36 36 x 5A, 6 x 20A

Circuits

SVTS C 10-U-A-06/36

Outside Diameter190.00 mm mmInside Diameter90.00 mm mmOverall Length (L)194.50 mm mmProtection ratingIP 65Data Transfert<=100Mbit/s</th>MountingThru-bore 90mm



Mechanical features

Nominal speed	>400 rpm
Temperature range	-20° C to $+80^{\circ}$ C (-40° C as option)
Contact	gold-gold (alloy)
Bearings	Miniature high-precision stainless steel ball bearings
Connector	-
Mounting	ABS



Electrical features

Voltage
Cables
Cables length

240 VDC/VAC Silver plated / PTFE insulated / colour coded 250 mm standard (other length on request)

Dielectric voltage strength	500VAC @ 60Hz @ 60 sec
Insulation resistance	>500MOhm/500VDC
Dynamic contact resistance	10mOhm @ 6VDC and 500mA (@ 5rpm)
Expected lifetime	10 ⁷ revolutions (depending on speed, environmetal conditions and size)

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.





- Ideal for electrical power and signal transmission
- Through hole 90 mm
- High data rate
- Low friction torque
- High lifetime and reliability
- Compliant to CE and ROHS

- Transmission of electric power/signals and fieldbuses in one unit
- Mountable on the shaft mitigating the need of interface parts
- Combinable with fluidic rotary joints and FORJ
- Cost-effective

Customisations

- Cables
- Materials
- Mechanical design
- Flange

product engineering services

expertise in connectivity