



Coreless BLDC motor.

High Power Density - High Efficiency - Cost Effective  
 Low noise - Low inductance - Good Heat Dissipation  
 Long Lifetime - No Cogging - Low Inertia - Robust

 Feature

| SVTN A 01-2232-18-S-O |              |
|-----------------------|--------------|
| Nominal voltage       | 18 V         |
| No load speed         | 12080 rpm    |
| No load current       | 86 mA        |
| Nominal speed         | 9937 rpm     |
| Nominal torque        | 6.000 mNm    |
| Nominal current       | 0.520 A      |
| Stall torque          | 33.800 mNm   |
| Stall current         | 2.550 A      |
| Max. efficiency       | 66.600 %     |
| Terminal resistance*  | 7.070 Ω      |
| Terminal inductance*  | 0.660 mH     |
| Torque constant       | 13.700 mNm/A |
| Speed constant        | 695 mNm/V    |

**Notice :** The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

## 2 POLE BRUSHLESS DC MOTORS

SVTN A 01-2232-18-S-O

|                          |                        |
|--------------------------|------------------------|
| Speed/torque gradient    | 357.00 rpm/mNm         |
| Mechanical time constant | 5.600 ms               |
| Rotor inertia            | 1.500 gcm <sup>2</sup> |

The benefits of this new technology are torque and high-speed when compared to the same sizing. The lack of cogging, a reduced ripple torque, a linear correlation between speed and torque, low inertia bring performance to a greater level in terms of power, dynamics by means of reduced weights and reduced dimensions. Servotecnica's brushless motors apply hall sensors as a standard option, in addition to having the magnetic encoder option. Thanks to the sensors it is possible to control rotation speed, and, thanks to the lack of cogging, provide high performance and accuracy.



### Advantages

Winding technology without metal bodies

Good heat dissipation and high overload capacity

Long life expectancy



### Benefits

Light and compact, easy integration

High reliability

Good return on investment



Zoning de la Rivière, 65  
7330 Saint-Ghislain (Belgium)

T : +32 (0)65 76 40 40  
E : service@pes-sa.com