


variables/V-color

Gripper | Parallel 3 jaws | CH81





Feature

CH81

Course	6 mm
Air consumption	1400 mm ³
Function	Double effet
Max cycle per minute	90 cycles
Gripping force*	82.000 N
Weight	0.210 kg
Max. weight of one attachment	0.040 kg
Type	Parallel 3 jaws



Operating conditions

Working media	Filtered air
Operating pressure	3 to 7 bar
Working temperature	5 to 60°C
Lubrication	Normally not required (but if necessary, use ISOVG32 compliant lubricant)
Repeatability*	Initial value : ± 0.1 mm, after 2 million cycles : ± 0.2 mm
Lifetime	2 million cycles (with balanced load on each finger)

Compact 3-Jaws Parallel type Cylindrical Gripper, stroke from 6 to 10mm

*The values of gripping force in the above table indicates pressure at the top edge of the fingers when gripping with pressure of 5 bar.

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

They are suited to receives long attachments thanks to fingers guide length.



Advantages

- Compact-Lightweight-Fast
- Silent mechanism
- Quick and simple integration
- Large opening angle
- Position sensors



Benefits

- No maintenance
- Very short cycle time
- Excellent power/volume ratio
- Low air consumption



product
engineering
services

expertise in connectivity