


variables/V-color

Micromotors | Slotless BLDC motor | SVTN A 02-1636-36-S-O





Feature

SVTN A 02-1636-36-S-O

| | |
|-----------------------------|-------------|
| Nominal voltage | 36 V |
| No load speed | 40760 rpm |
| No load current | 72 mA |
| Nominal speed | 37406 rpm |
| Nominal torque | 5.000 mNm |
| Nominal current | 0.670 A |
| Stall torque | 60.800 mNm |
| Stall current | 7.300 A |
| Max. efficiency | 81.200 % |
| Terminal resistance* | 4.900 ? |
| Terminal inductance* | 0.240 mH |
| Torque constant | 8.350 mNm/A |
| Speed constant | 1143 mNm/V |

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

High-Speed Brushless DC Motors

SVTN A 02-1636-36-S-O

| | |
|---------------------------------|----------------|
| Speed/torque gradient | 671.00 rpm/mNm |
| Mechanical time constant | 3.900 ms |

SVTN A 02-1636-36-S-O

Rotor inertia

0.550 gcm²

Typically employed in the medical field for surgical tools, these motors merge the SVTN A Series characteristics to an optimized project for high-speed functions. Thanks to a precise balancing of the rotor and the use of special bearings, maximum stability, and low noise are guaranteed.



Advantages

- Winding technology without metal bodies
- Good heat dissipation and high overload capacity
- Long life expectancy



Benefits

- Light and compact, easy integration
- High reliability
- Good return on investment



pes

product
engineering
services

expertise in connectivity