## MICROMOTORS | SLOTLESS BLDC MOTOR | SVTN A 02-1656-30-S-O



Slotless BLDC motor

High Speed - Long Lifespan - Cost Effective Low Inertia - High Efficiency - Low Noise - High Reliability

## Feature

	SVTN A 02-1656-30-S-O
Nominal voltage	30 V
No load speed	40775 rpm
No load current	89 mA
Nominal speed	38438 rpm
Nominal torque	6.000 mNm
Nominal current	0.950 A
Stall torque	105.000 mNm
Stall current	15.100 A
Max. efficiency	85.200 %
Terminal resistance*	1.990 Ω
Terminal inductance*	0.140 mH
Torque constant	6.980 mNm/A
Speed constant	1367 mNm/V

**Notice**: The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

## HIGH-SPEED BRUSHLESS DC MOTORS

	SVTN A 02-1656-30-S-O
Speed/torque gradient	390.00 rpm/mNm
Mechanical time constant	2.500 ms
Rotor inertia	0.610 gcm²

Typically employed in the medical field for surgical tools, these motors merge the SVTN A Series characteristics to an optimized project for high-speed functions. Thanks to a precise balancing of the rotor and the use of special bearings, maximum stability, and low noise are guaranteed.



Benefits

Winding technology without metal bodies

Good heat dissipation and high overload capacity

Long life expectancy

Light and compact, easy integration

High reliability

Good return on investment

