## MICROMOTORS | CORELESS BLDC MOTORS | SVTN A 03-1228-06-S-1



Coreless BLDC motor

Long Lifetime - High Efficiency - Low Noise - High Reliability No Cogging - Low Inertia - Cost-effective

## Feature

	SVTN A 03-1228-06-S-1
Nominal voltage	6 V
No load speed	31000 rpm
No load current	140 mA
Nominal speed	27755 rpm
Nominal torque	0.500 mNm
Nominal current	0.420 A
Stall torque	4.780 mNm
Stall current	2.860 A
Max. efficiency	60.600 %
Torque constant	1.780 mNm/A
Speed constant	5374 mNm/V

**Notice**: The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

## 2 POLE BRUSHLESS DC MOTORS WITH INTEGRATED ELECTRONICS

	SVTN A 03-1228-06-S-1
Speed/torque gradient	6350.00 rpm/mNm
Mechanical time constant	11.300 ms
Rotor inertia	0.200 gcm <sup>2</sup>

The benefits of this technology join the simplicity of use of a brushed DC motor with the longevity of a brushless motor, maintaining cost-effectiveness and ease of integration. The lack of cogging is typical of the coreless motors and guarantees a reduced ripple torque, a linear correlation between torque, speed, and low inertia. The miniaturization of the electronics allows maintaining the diameter of the motor unvaried with a slight increase in length.





Winding technology without metal bodies

Good heat dissipation and high overload capacity

Long life expectancy

Light and compact, easy integration

High reliability

Good return on investment

No need for external drive

