

variables/V-color

Gripper | Angular 2 jaws | CH25





Feature

CH25

Course	14-7°
Air consumption	400 mm ³
Function	Normal open
Max cycle per minute	60 cycles
Weight	0.034 kg
Type	Angular 2 jaws



Operating conditions

Working media	Filtered air
Operating pressure	3 to 7 bar
Working temperature	5 to 60°C
Lubrication	Normally not required (but if necessary, use ISOVG32 compliant lubricant)
Repeatability*	Initial value : ± 0.1 mm, after 2 million cycles : ± 0.2 mm
Lifetime	2 million cycles (with balanced load on each finger)

Angular Type Small Gripper, angle 14~-7°

*The values of gripping force in the above table indicates pressure at the top edge of the fingers when gripping with pressure of 5 bar.

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

This gripper can be easily integrated and oriented with its optionnal mounting support.



Advantages



Benefits

- Compact-Lightweight-Fast
- Silent mechanism
- Quick and simple integration
- Large opening angle
- Position sensors
- No maintenance
- Very short cycle time
- Excellent power/volume ratio
- Low air consumption



pes

product
engineering
services

expertise in connectivity