
variables/V-color

Micromotors | Coreless DC Motors | SVTN B 01-1215-7.4-S-WM





SVTN B 01-1215-7.4-S-WM Nominal voltage 7 V No load speed 28000 rpm No load current 35 mA Nominal speed 22400 rpm Nominal torque 0.700 mNm Nominal current 0.300 A Stall torque 3.600 mNm 1.500 A Stall current Max. efficiency 68.400 % **Terminal resistance*** 4.930? Terminal inductance* 23.000 mH **Torque constant** 2.450 mNm/A **Speed constant** 3783 mNm/V

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

2 Pole Brushed DC Motors

SVTN B 01-1215-7.4-S-WM

Speed/torque gradient7861.00 rpm/mNmMechanical time constant9.100 ms

SVTN B 01-1215-7.4-S-WM

Rotor inertia

0.110 gcm²

The specific design construction of a coreless DC motor provides several advantages over the traditional, iron core, technology. A first added value it is given by rotor lower mass and inertia, so very rapid acceleration and deceleration rates are possible. Furthermore, the lack of iron reduces "iron losses" to provide higher efficiencies (up to 90 percent) than traditional DC motors. Last, but not least, the coreless design reduces winding inductance, so sparking between the brushes and commutator is reduced, increasing motor life and reducing electromagnetic interference (EMI). Our Coreless DC Motors are available on a wide range of sizes and we can show high flexibility on custom requirements.





- Winding technology without metal bodies
- Good heat dissipation and high overload capacity
- Long life expectancy

- Light and compact, easy integration
- High reliability
- Good return on investment



product engineering services

expertise in connectivity