
Micromotors | Coreless DC Motors | SVTN B 01-1524-12-D-WM





SVTN B 01-1524-12-D-WM

Nominal voltage 12 V

No load speed 11800 rpm

No load current 11 mA

Nominal speed 9440 rpm

Nominal torque 1.700 mNm

Nominal current 0.200 A

Stall torque 8.700 mNm

Stall current 0.900 A

Max. efficiency 79.300 % Terminal resistance* 13.040 ?

Terminal inductance* 0.230 mH

Torque constant 9.600 mNm/A

Speed constant 983 mNm/V

Notice: The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

2 Pole Brushed DC Motors

SVTN B 01-1524-12-D-WM

Speed/torque gradient 1352.90 rpm/mNm

Mechanical time constant 11.900 ms

SVTN B 01-1524-12-D-WM

Rotor inertia

0.840 gcm²

The specific design construction of a coreless DC motor provides several advantages over the traditional, iron core, technology. A first added value it is given by rotor lower mass and inertia, so very rapid acceleration and deceleration rates are possible. Furthermore, the lack of iron reduces "iron losses" to provide higher efficiencies (up to 90 percent) than traditional DC motors. Last, but not least, the coreless design reduces winding inductance, so sparking between the brushes and commutator is reduced, increasing motor life and reducing electromagnetic interference (EMI). Our Coreless DC Motors are available on a wide range of sizes and we can show high flexibility on custom requirements.



Advantages



Benefits

- Winding technology without metal bodies
- Good heat dissipation and high overload capacity
- Long life expectancy

- Light and compact, easy integration
- High reliability
- Good return on investment



expertise in connectivity