



 Feature

	Master Adaptor	Tool Adaptor
Reference	S5.1R-XXX	S5.1T-XXX
Payload	500 kg	
Moment - Mx, My	2937 Nm	
Moment - Mz	3084 Nm	
Size	60x310x358	60x310x358
Weight	11.340 kg	8.660 kg
Couple/uncouple port	1/4" BSPP	n/a
Repeatability - X, Y	0.020 mm	
Repeatability - Z	0.013 mm	

 Operating conditions

Operating temperature	5-60°C
Operating pressure	6 bar ±1
User pneumatic pressure	6 bar ±1

# SIGMA THE FOOLPROOF TOOL CHANGER RANGE

Heavy Payload Tool Changers are gathered within Sigma Series. They allow handling payloads from 350kg till 800kg and are particularly suited for various applications such as spot welding, material handling, machine loading/unloading, mold changing, docking systems, pallet coupling systems, pick and place operations, press transfer.

Sigma Series tool changers have a modular design allowing them to suit any kind of application. Indeed, our range of standard module coupled with our custom modules offer increase the Sigma tool changers capabilities enabling them to meet many different needs.

Sigma 5.1 tool changers have a unique six-sided design allowing to accomodate more utilities. The wide range of supported communication systems and their ability to connect directly to your robot face plate, elminitaing adaptor plate make them a easy-to-integrate solution while meeting the most complex applicative needs.



## Advantages

Unique wear-compensating, fail-safe cam latching mechanism

Emergency manual unlock feature

Higher payload capacity – up to 500 kg

Unique six-sided design accommodates more utilities



## Benefits

A Sigma 3.1 and Sigma 5.1 common profile provides modularity and allows for interchangeability of utility modules

Eliminates adaptor plates for lower weights, and increased strength and efficiency

Low profile reduces inertial forces

Supports wide variety of servo tools and bus communications



Zoning de la Rivière, 65  
7330 Saint-Ghislain (Belgium)

T : +32 (0)65 76 40 40  
E : service@pes-sa.com