



Ethernet/I Body Flexor control module (3 Control valves, 3 pressure sensors, TC control by remote I/O module, safety sensor "Tool presence", Ethernet/IP connection to tool), 7/8" male 5pins (24VDC), D-Coded M12-4 pins connector (Ethernet/IP) - Tool Changer Valves with Output 24VDC , two M12 cod A 5 pins male and female connector and one female connector 7/8" (Power) for Can Open BUS

 Feature

S-EM-R-E-ETH-BF-V19-3VS-01-A	
Type	Electrical module
Weight	1.960 kg
Size	65 x 234 x 148 mm
Pass Through Utilities	2 x KJ06 1/8" 6mm 1 x KQ2 1/8" 8mm
Material	Aluminum, Stainless Steel, Gold, Plastic, Copper
Connector	1 x 7/8" 5CTS 1 x M12 COD-D 4CTS Profinet
Sensor	Tool presence safety switch
Safety Loop	Pneumatic safety loop 3EV+3 pressure switches

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

A CUSTOM BODY FLEXOR 3VS VERSION CONTROL MODULE

Along with the standard offer of pneumatic and electrical modules, PES proposes engineering capabilities for developing custom electrical/pneumatic modules or accessories for Sigma Series tool changers. We offer a wide range of off-the-shelf custom modules enhancing Sigma tool changers communication capabilities or safety and if needed, we will be pleased to adapt our product to your specific requirements. Standard Air/Water modules are listed below. Do not hesitate to contact us to share your specific requirements in order to find the right solution that meets your needs



Advantages



Benefits



pes

product
engineering
services

Zoning de la Rivière, 65
7330 Saint-Ghislain (Belgium)

T : +32 (0)65 76 40 40
E : service@pes-sa.com