MAGNETIC TOOL | LAY SERIES | PLAY50X4 2.0



The "LAY" signifies Linear Array: designed for applications where stability and power are important.



	PLAY50X4 2.0
Weight	11.30 kg
Max Breakaway ₁	994.30 kg
Working Load ₂	200.00 kg
Optimal material thickness	9.50 mm
Max shear	238.00 kg
Magnetic pole footprint	239x71 mm

¹ Safety factor 2:1

Notice: The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

² Safety factor 4:1

MULTIPLE MAGNETS FOR HANDLING POWER AND CONTROL

Ideal for long cylinders, tubing and rough surface finishes, the multiple magnetic fields in LAY units ensure strong holding forces on thin material. Each unit comes with replaceable pole shoes for improved on-site serviceability.



Benefits

Double effect pneumatic actuator offering high duty cycle

Custom pole shoes offer mechanical function integration capability

Linear array of multiple magnets for increased power and increased handling controll of long parts with a limited energy consumption

Intrinsic safety thanks to 183° movement for natural Istop locking

Limited maintenance costs

Reduced cycle time

Controlled integration costs



Zoning de la Rivièrette, 65 7330 Saint-Ghislain (Belgium) T:+32 (0)65 76 40 40 E:service@pes-sa.com