



Make your application stand out with a precise, versatile, all-in-one solution.

System Data

GMI-ROT-055-B11-AL	
Type	Axial, frameless, true absolute Giant Magneto Impedance encoder GMITechnology-FLUX GmbH proprietary
Standard Resolution	21 bits
ENOB in entire mounting tolerance range	20 bits
High Accuracy	$\pm 36''$, $\pm 0.010^\circ$, $\pm 175\mu\text{rad}$
Standard Accuracy	$\pm 50''$, $\pm 0.014^\circ$, $\pm 244\mu\text{rad}$
Thickness	7.50
Hysteresis	none
Repeatability	1 resolution count
Position update rate and signal latency	Real-time
Power-up Time	max. 0.8 sec

Electrical Data

Supply voltage	OptionAV: min. 4.35Vdc. max. 36Vdc Option5V: min. 4.35Vdc. max. 6Vdc Option24V: min. 6Vdc. Max. 30Vdc
----------------	---

Reverse polarity protection	yes
Current Consumption	max. 150 mA @ 25 Vdc, max. 140 mA @ 24 Vdc

Mechanical Data

Stator Base Material	Stainless steel (option-ST) CTE~10ppm/°C Aluminum (option-AL) CTE~24ppm/°C
Stator Weight	45.22 g
Rotor Base Material	Stainless steel (option-ST) CTE~10ppm/°C Aluminum (option-AL) CTE~24ppm/°C
Rotor Weight	15.80 g
Vibration	EN 60068-2-6, 20 g, 55 .. 2000 Hz
Shock	EN 60068-2-27, 200 g, 6 ms

Mounting Tolerances

Nominal Axial (air-gap)	0.30 mm
Axial Tolerance	-0.20 mm, +0.50 mm
Radial Tolerances	0.20 mm

Environmental Data

Temperature Range - Standard Operating	-20°C .. +85°C
Temperature Range - Standard Storage	-20°C .. +85°C
Temperature Range - Extended Operating	-40°C .. +105°C
Temperature Range - Extended Storage	-55°C .. +125°C
Ingress Protection	IP67
EMC Immunity	complies with EN IEC 61000-6-2
EMC Emission	complies with EN IEC 61000-6-4

Advantages

Plug-n-play

No field calibration required

Wide mounting tolerances

High accuracy

Benefits

Low installation cost

Low integration effort

Easy installation