

Slip ring specially suited to transmit critical signals, such as hi frequency and data rate, low current and voltages (strain gauges, thermocouples, measuring equipment, etc.)

Feature

	SVTS A 01-U-X-00/06
Circuits	6 x 1 A
Outside Diameter	12.50 mm mm
Overall Length (L)	21.50 mm mm
Protection rating	IP 65
Data Transfert	<=100Mbit/s
Mounting	Flange / Capsule

Mechanical features

Nominal speed	0-250 rpm
Temperature range	-20°C to +80°C (-40°C as option)
Contact	gold-gold (alloy)
Bearings	Miniature high-precision stainless steel ball bearings
Connector	-
Mounting	Al

Electrical features

Voltage	240 VDC/VAC
Cables	Silver plated / PTFE insulated / colour coded
Cables length	250 mm standard (other length on request)
Dielectric voltage strength	500VAC @ 60Hz @ 60 sec
Insulation resistance	>500MOhm/500VDC
Dynamic contact resistance	10mOhm @ 6VDC and 500mA (@ 5rpm)
Expected lifetime	10 ⁷ revolutions (depending on speed, environmetal conditions and size)

Notice: The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

Advantages



Ideal for video, high frequency signals
High data rate
Gold alloy rings and brushes
Low friction torque
High lifetime and reliability
Combinable with fluidic rotary joints and FORJ

Optimal signal transmission (gold-gold technology)

Cost-effective

Customisations

- Cables
- Materials
- Mechanical design

• Flange

