



 Feature

	Master Adaptor	Tool Adaptor
Reference	S8.1R-XXX	S8.1T-XXX
Payload	800 kg	
Moment - Mx, My	7796 Nm	
Moment - Mz	7796 Nm	
Size	60x310x358 mm	60x310x358 mm
Weight	21.180 kg	11.840 kg
Couple/uncouple port	1/4" BSPP	n/a
Repeatability - Z	0.013 mm	

 Operating conditions

Operating temperature	5-60°C
Operating pressure	6 bar ±1
User pneumatic pressure	6 bar ±1

SIGMA THE FOOLPROOF TOOL CHANGER RANGE

Heavy Payload Tool Changers are gathered within Sigma Series. They allow handling payloads from 350kg till 800kg and are particularly suited for various applications such as spot welding, material handling, machine loading/unloading, mold changing, docking systems, pallet coupling systems, pick and place operations, press transfer.

Sigma Series tool changers have a modular design allowing them to suit any kind of application. Indeed, our range of standard module coupled with our custom modules offer increase the Sigma tool changers capabilities enabling them to meet many different needs.

Sigma 8.1 tool changers have a unique six-sided design allowing to accomodate more utilities. The wide range of supported communication systems and their ability to connect directly to your robot face plate, elminitaing adaptor plate make them a easy-to-integrate solution while meeting the most complex applicative needs.



Advantages

Unique wear-compensating, fail-safe cam latching mechanism

Emergency manual unlock feature

Higher payload capacity – up to 800 kg

Unique six-sided design accommodates more utilities



Benefits

A Sigma 3.1 and Sigma 5.1 common profile provides modularity and allows for interchangeability of utility modules

Eliminates adaptor plates for lower weights, and increased strength and efficiency

Low profile reduces inertial forces

Supports wide variety of servo tools and bus communications



pes

product
engineering
services

Zoning de la Rivière, 65
7330 Saint-Ghislain (Belgium)

T : +32 (0)65 76 40 40
E : service@pes-sa.com