



With moments trip point from 7.5 to 290 Nm, medium payload collision sensors will be the most appropriate models for your applications such as cutting or gripping.

## Feature

QS-200	
Repeatability - X, Y	0.025 mm
Repeatability - Z	0.013 mm
Rotational Repeatability	$\pm 0.024^\circ$
Axial Compliance Vertical	5.200 mm
Compliance Angle	$5^\circ$
Rotary Compliance	No limit
Torque Trip Point	7.5 - 45.2 Nm
Moment Trip Point	5.9 - 32.4 Nm
Weight	0.680 kg
Diameter	97.000 mm
Profile	43.500 mm
Center of Mass	25.700 mm
Average response time	4-7 ms
Dust Protection	Foam collar supplied
Switch	High reliability aircraft snap acting type. UL/CSA approved. Average cycle life : 7 million cycles

# COLLISION DETECTOR QS-200: PROTECT YOUR EQUIPMENT IN DEMANDING ENVIRONMENTS

## Operating conditions

Operating Pressure	1.0 - 6.0 bar
Operating Temperature	Min. 0°C / Max. 70°C

**Notice :** The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

- Dynamically variable collision sensor that operate on air pressure. Breakaway threshold adjusts to match the working force ranges of robot/application
- Non compressive, metal to metal seal for reliable and consistent operation
- Opening of QuickSTOP air chamber at impact, pressure exhaust and switch signal stop the robot

## Advantages

Senses angular and compressive forces.  
QuickSTOP's unique design offers protection in X, Y and Z axis

Linear and angle strokes available to remove the forces from end of arm tooling and robot wrist at trip point

Performance readiness is monitored by QuickSTOP. When pressurized, the switch indicates that the QuickSTOP is reset in proper position

## Benefits

Minimize down time, quick reset, no need for recalibration, stopping robot at source of impact allows for easy identification of cause

Minimize robot and expensive end of arm tooling damage during robot programming. A must for any education or robot training cell

Easy to implement, simple to adjust pressure level according application, quick return on investment



product  
engineering  
services

Zoning de la Rivière, 65  
7330 Saint-Ghislain (Belgium)

T : +32 (0)65 76 40 40  
E : service@pes-sa.com