

variables/V-color

Rotary Union | 10 passages | GP(S) 20110



The GP and GPS (stainless steel) Series multiple passage rotary unions are available in 2, 3, 4, 6, 8, 10 & 12 passage models. They meet highly demanding requirements in terms of pressure and rotating speed for applications with liquid, air or vacuum. Modified or specialized configurations are also available.



Feature

GP(S) 20110

Type	Hydraulic series
Passages	10 passages
Connector	1/4" NPT
Overall Diameter	93.600 mm
Overall length	245.000 mm
Min Torque	29.380 Nm
Passage Size	6.300 mm
Maximum Pressure ¹	51.5 MPa (515 bar)
Maximum Vacuum ¹	30 HG
Max Speed ¹	500 rpm
Temperature Range ¹	-18°C à 105°C

¹ Values are dependent on a combination of all application parameters.
Please consult PES.

Versatile, efficient and multichannel



General information

GP(S) 20110

Connection Sizes	1/8", 1/4", 3/8", 1/2", 3/4", 1" NPT
-------------------------	--------------------------------------

GP(S) 20110

Connection type	NPT & BSPP threads standard. SAE, NPTF, and other thread options are available on a custom basis.
Plating and Coating	Black oxide plating is standard. Anodized, E-Nickel, Chrome, Nitride, Ceramic and other specialty platings are available as custom options.
Material	Carbon steel is the standard material for the GP Series, Stainless Steel is the standard material for the GPS Series. Aluminum, Brass, and other materials are available on a custom basis.
Mounting	The GP series unions have a unique shaft configuration that consists of individual female tapped passages with an o-ring gland around each for optional flange mounting. There are also tapped holes on the end of the housing for mounting the assembly.

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

All GP and GPS Series rotary unions incorporate exclusive DynaSeal™ seals, which are suitable for vacuum and bidirectional pressures up to 51.5 MPa (515 bar). All passages are individually sealed to allow use with dissimilar medias. They can be combined with a wide range of standard or custom slip rings.



Advantages

- Multipurpose solution for air, gas, oil, water or vacuum
- Easy integration
- High performances (pressure, rotating speed)



Benefits

- Avoid the need of complex piping arrangements
- Increased machinery performances
- Paiping maintenance mitigated



pes

product
engineering
services

expertise in connectivity