



With moments trip point from 150 to 2300 Nm, heavy payload collision sensors will be the most appropriate models for your applications such as handling of larger and heavier items.

 Feature

QS-7500	
Repeatability - X, Y	0.038 mm
Repeatability - Z	0.013 mm
Rotational Repeatability	± 0.029 °
Axial Compliance Vertical	12.680 mm
Compliance Angle	4 °
Rotary Compliance	25°
Torque Trip Point	1007 - 2098 Nm
Moment Trip Point	472 - 1049 Nm
Weight	16.800 kg
Diameter	288.000 mm
Profile	115.000 mm
Center of Mass	73.000 mm
Average response time	4-18 ms
Dust Protection	Foam collar supplied
Switch	High reliability aircraft snap acting type. UL/CSA approved. Average cycle life : 7 million cycles

COLLISION DETECTOR QS-7500: PROTECT YOUR EQUIPMENT AND BOOST YOUR PRODUCTIVITY. UNIQUE DESIGN FOR ALL INDUSTRIES.

Operating conditions

Operating Pressure	1.0 - 6.0 bar
Operating Temperature	Min. 0°C / Max. 100°C

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

- Dynamically variable collision sensor that operate on air pressure. Breakaway threshold adjusts to match the working force ranges of robot/application
- Non compressive, metal to metal seal for reliable and consistent operation
- Opening of QuickSTOP air chamber at impact, pressure exhaust and switch signal stop the robot

Advantages

Senses angular and compressive forces.
QuickSTOP's unique design offers protection in X, Y and Z axis

Linear and angle strokes available to remove the forces from end of arm tooling and robot wrist at trip point

Performance readiness is monitored by QuickSTOP. When pressurized, the switch indicates that the QuickSTOP is reset in proper position

Benefits

Minimize down time, quick reset, no need for recalibration, stopping robot at source of impact allows for easy identification of cause

Minimize robot and expensive end of arm tooling damage during robot programming. A must for any education or robot training cell

Easy to implement, simple to adjust pressure level according application, quick return on investment



product engineering services
Zoning de la Rivière, 65
7330 Saint-Ghislain (Belgium)

T : +32 (0)65 76 40 40
E : service@pes-sa.com