


variables/V-color

Slip Ring | 60 circuits | SVTS C 06-S-A-12/48



Slip ring for transmission of electrical power and/or electrical signals with through hole for shaft or rotary union.



Feature

Circuits

SVTS C 06-S-A-12/48

48 x 5A, 12 x 20A

SVTS C 06-S-A-12/48

Outside Diameter	120.00 mm mm
Inside Diameter	50.00 mm mm
Overall Length (L)	210.50 mm mm
Protection rating	IP 65
Data Transfert	<=100Mbit/s
Mounting	Thru-bore 50mm



Mechanical features

Nominal speed	>400 rpm
Temperature range	-20°C to +80°C (-40°C as option)
Contact	gold-gold (alloy)
Bearings	Miniature high-precision stainless steel ball bearings
Connector	-
Mounting	ABS



Electrical features

Voltage	240 VDC/VAC
Cables	Silver plated / PTFE insulated / colour coded
Cables length	250 mm standard (other length on request)

Dielectric voltage strength	500VAC @ 60Hz @ 60 sec
Insulation resistance	>500MOhm/500VDC
Dynamic contact resistance	10mOhm @ 6VDC and 500mA (@ 5rpm)
Expected lifetime	10 ⁷ revolutions (depending on speed, environmental conditions and size)

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.



Advantages



Benefits

- | | |
|--|--|
| <ul style="list-style-type: none"> • Ideal for electrical power and signal transmission • Through hole 50 mm • High data rate • Low friction torque • High lifetime and reliability • Compliant to CE and ROHS | <ul style="list-style-type: none"> • Transmission of electric power/signals and fieldbuses in one unit • Mountable on the shaft mitigating the need of interface parts • Combinable with fluidic rotary joints and FORJ • Cost-effective |
|--|--|

Customisations

- Cables
- Materials
- Mechanical design
- Flange



p e s

product
engineering
services

expertise in connectivity