



The 'AR' contains a rectangular housing with removable pole shoes, which work well with irregularly shaped surfaces: pipes, cylinders, etc. This tool is the best choice when no flat area exists on the target. With three possible work faces, the tools provide tremendous flexibility for multiple end of arm applications.

Feature

AR110 HDC HT	
Weight	25.80 kg
Max Breakaway ¹	1530.90 kg
Working Load ²	382.70 kg
Optimal material thickness	38.10 mm
Max shear	95.70 kg
Overall Height	375.70 mm
Magnetic pole footprint	150x113.9 mm

¹ Safety factor 2:1

² Safety factor 4:1

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

THE MULTIPURPOSE, HIGH PERFORMANCE A SAFE MAGNETIC GRIPPING

Temperature of the operated surface can reach 80°C for Classic versions and 220°C or higher for High Heat versions (please contact us of high temperature applications). Note: You may have to design and fabricate custom pole shoes depending on your application for optimal performances

Advantages

Double effect pneumatic actuator offering high duty cycle

Custom pole shoes offer mechanical function integration capability

Intrinsic safety thanks to 183° movement for natural lstop locking

Benefits

Limited maintenance costs

Reduced cycle time

Controlled integration costs