Magnetic Tool | LAY Series | PLAY70x3 MDC HT





PLAY70x3 MDC HT

Weight 22.20 kg

Max Breakaway 1 1304.00 kg

Working Load 2 326.00 kg

Optimal material thickness 12.70 mm

Max shear 90.70 kg

Overall Height 301.00 mm

Magnetic pole footprint 255x97.6 mm

Notice: The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

Multiple magnets for handling power and control

Ideal for long cylinders, tubing and rough surface finishes, the multiple magnetic fields in LAY units ensure strong holding forces on thin material. Each unit comes with replaceable pole shoes for improved onsite serviceability.

¹ Safety factor 2:1

² Safety factor 4:1





- Double effect pneumatic actuator offering high duty cycle
- Custom pole shoes offer mechanical function integration capability
- Linear array of multiple magnets for increased power and increased handling controll of long parts with a limited energy consumption
- Intrinsic safety thanks to 183° movement for natural 1stop locking

- Limited maintenance costs
- Reduced cycle time
- Controlled integration costs



expertise in connectivity