



The even more compact T20 is a miniature version of our T30, featuring similar high precision and repeatable mounting and manual override features

Feature

	T20
Weight	0.19 kg
Max Breakaway ¹	34.00 kg
Working Load ²	8.50 kg
Optimal material thickness	4.00 mm
Max shear	10.00 kg
Overall Height	54.00 mm
Magnetic pole footprint	36x21 mm

¹ Safety factor 2:1

² Safety factor 4:1

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

COMPACT, VERSATILE, HIGH PRECISION REPEATABLE MOUNTING MANUAL OVERRIDE

The Magswitch T20 is compact and powerful, boasting cutting edge technology enhancements and precision mounting interfaces. This tool is great for fixtures, pin locating, and thin part material handling. Additional custom pole shoe geometry allows for extreme flexibility in applications.

Advantages

In addition to all AR series advantages :

Larger air ports (G1/8) for increased compatibility and robust connections

Manufactured to precision tolerances with top face NAAMS mounting

Tool is equipped with externally accessible manual override

Benefits

Limited maintenance costs

Reduced cycle time

Controlled integration costs