



The T30, featuring similar high precision and repeatable mounting and manual override features

## Feature

	T30
Weight	0.61 kg
Max Breakaway <sup>1</sup>	73.00 kg
Working Load <sup>2</sup>	18.25 kg
Optimal material thickness	6.00 mm
Max shear	17.60 kg
Overall Height	79.00 mm
Magnetic pole footprint	54x31 mm

<sup>1</sup> Safety factor 2:1

<sup>2</sup> Safety factor 4:1

**Notice :** The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

# COMPACT, VERSATILE, HIGH PRECISION REPEATABLE MOUNTING MANUAL OVERRIDE

Magswitch T30 is compact and powerful boasting cutting edge technology enhancements and precision mounting interfaces. These tools are great for fixtures, pin locating and thin part material handling. Additional custom pole shoe geometry allows for extreme flexibility in applications. This tool is a precision fit for your next project!



## Advantages

In addition to all AR series advantages :

Larger air ports (G1/8) for increased compatibility and robust connections

Manufactured to precision tolerances with top face NAAMS mounting

Tool is equipped with externally accessible manual override



## Benefits

Limited maintenance costs

Reduced cycle time

Controlled integration costs



Zoning de la Rivière, 65  
7330 Saint-Ghislain (Belgium)

T : +32 (0)65 76 40 40  
E : service@pes-sa.com