



Slip ring for transmission of electrical power and/or electrical signals with through hole for shaft or rotary union.

## Feature

SVTS C 08-U-A-12/60	
Circuits	60 x 5A, 12 x 20A
Outside Diameter	155.00 mm mm
Inside Diameter	70.00 mm mm
Overall Length (L)	274.00 mm mm
Protection rating	IP 65
Data Transfer	<=100Mbit/s
Mounting	Thru-bore 70mm

## Mechanical features

Nominal speed	>400 rpm
Temperature range	-20°C to +80°C (-40°C as option)
Contact	gold-gold (alloy)
Bearings	Miniature high-precision stainless steel ball bearings
Connector	-
Mounting	ABS

## Electrical features

Voltage	240 VDC/VAC
Cables	Silver plated / PTFE insulated / colour coded
Cables length	250 mm standard (other length on request)
Dielectric voltage strength	500VAC @ 60Hz @ 60 sec
Insulation resistance	>500MΩ/500VDC
Dynamic contact resistance	10mΩ @ 6VDC and 500mA (@ 5rpm)
Expected lifetime	10 <sup>7</sup> revolutions (depending on speed, environmental conditions and size)

**Notice :** The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

## Advantages

Ideal for electrical power and signal transmission

Through hole 70 mm

High data rate

Low friction torque

High lifetime and reliability

Compliant to CE and ROHS

## Benefits

Transmission of electric power/signals and fieldbuses in one unit

Mountable on the shaft mitigating the need of interface parts

Combinable with fluidic rotary joints and FORJ

Cost-effective

## Customisations



Zoning de la Rivière, 65  
7330 Saint-Ghislain (Belgium)

T : +32 (0)65 76 40 40  
E : [service@pes-sa.com](mailto:service@pes-sa.com)