



Technical specification		
	Power	Signal
Circuits	6	2
Rated voltage	400V dc	400V dc
Rated current	20A	5A
Dielectric strength	min 800Vac@50Hz, 60s	
Insulation resistance	min 500M Ohm/500V dc	
Dynamic contact resistance	max 0,01 Ohm	
Contact material	Precious metals	
Frame material	Engineering plastic	
Operating temperature	-20°C~+80°C	
Operating speed	0-400 rpm	
Sealing	IP51	

	Total	Power	Signals	Weight(kg)	Power	Signals
		20A	5A		Faston	Faston
SVTS B 02-S-A-06/00	6	6	-	0,15	0.8x6.3	-
SVTS B 02-S-A-06/02	8	6	2	0,15	0.8x6.3	0.8x2.8

TRATTAMENTO TREATMENT:		4			
		3	15/01/2018	Aggiornati dati tabella "Technical Specification"	
		2	01/06/2016	Aggiornamento Part Number	
		1	02/11/2015	Aggiunti valori di massa	
		0	16/10/2012	Prima emissione	
MATERIALE MATERIAL:		REV. Nr REV N°	DATA/DATE	DESCRIZIONE/DESCRIPTION	
PESO WEIGHT		Tolleranze/Tolerances UNI EN 22768-1			DRAWING Nr. - DISEGNO N°  000-083
		TITLE - TITOLO  SVTS B 02			
		FINE			CODICE SERVOTECNICA  -
		MEDIA		x	
		GROSSOLANA			
		MOLTO GROSSOLANA			
		DATE DATA	16/10/2012	SH. FG.	1
		CHECK CONTR.	AB	DRAW. DIS.	AB
		FORM A3			
PROPERTY PROPRIETÀ		SERVOTECNICA S.P.A. - VIA MAJORANA,4 - NOVA MILANESE(MB) - www.servotecnica.com			